

Package: LKT (via r-universe)

September 13, 2024

Title Logistic Knowledge Tracing

Version 1.7.0

Description Computes Logistic Knowledge Tracing ('LKT') which is a general method for tracking human learning in an educational software system. Please see Pavlik, Eglington, and Harrel-Williams (2021) <<https://ieeexplore.ieee.org/document/9616435>>. 'LKT' is a method to compute features of student data that are used as predictors of subsequent performance. 'LKT' allows great flexibility in the choice of predictive components and features computed for these predictive components. The system is built on top of 'LiblineaR', which enables extremely fast solutions compared to base glm() in R.

License GPL-3

Encoding UTF-8

LazyData true

VignetteBuilder knitr

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Depends R (>= 3.5.0), SparseM (>= 1.83), methods, Matrix, data.table (>= 1.13.2), LiblineaR (>= 2.10-8)

Imports glmnet (>= 4.0-2), glmnetUtils (>= 1.1.8), lme4 (>= 1.1-23), cluster (>= 2.1.3), pROC (>= 1.16.2), crayon, HDInterval (>= 0.2.2)

Suggests rmarkdown, knitr, utils, caret, ggplot2

Repository <https://optimal-learning-lab.r-universe.dev>

RemoteUrl <https://github.com/optimal-learning-lab/lkt>

RemoteRef HEAD

RemoteSha 44a46639a5faf51fe44aae59e45300a5936a4006

Contents

buildLKTModel	2
computefeatures	4
computeSpacingPredictors	4
countOutcomeold	5
largerawsample	5
LASSOLKTData	6
LASSOLKTModel	7
LKT	8
LKT_HDI	10
predict_lkt	11
samplelkt	12
smallSet	12
ViewExcel	13
Index	14

buildLKTModel	<i>buildLKTModel</i>
---------------	----------------------

Description

Forward and backwards stepwise search for a set of features and components with tracking of nonlinear parameters.

Usage

```
buildLKTModel(
  data,
  usefolds = NA,
  allcomponents,
  allfeatures,
  currentcomponents = c(),
  specialcomponents = c(),
  specialfeatures = c(),
  forv,
  bacv,
  preset = NA,
  presetint = T,
  currentfeatures = c(),
  verbose = FALSE,
  currentfixedpars = c(),
  maxitv = 10,
  interc = FALSE,
  forward = TRUE,
  backward = TRUE,
  metric = "BIC",
```

```

  removefeat = c(),
  removecomp = c()
)

```

Arguments

<code>data</code>	is a dataset with <code>Anon.Student.Id</code> and <code>CF.ansbin</code> .
<code>usefolds</code>	Numeric Vector Specifies the folds for model fitting in LKT; the features are still calculated across all folds to compute test fold fit externally
<code>allcomponents</code>	is search space for LKT components
<code>allfeatures</code>	is search space for LKT features
<code>currentcomponents</code>	components to start search from
<code>specialcomponents</code>	add special components (not crossed with features, only paired with special features 1 for 1)
<code>specialfeatures</code>	features for each special component (not crossed during search)
<code>forv</code>	the minimum amount of improvement needed for the addition of a new term
<code>bacv</code>	the maximum amount of loss for a term to be removed
<code>preset</code>	One of "static", "AFM", "PFA", "advanced", "AFMLLTM", "PFALLTM", "advancedLLTM"
<code>presetint</code>	should the intercepts be included for preset components
<code>currentfeatures</code>	features to start search from
<code>verbose</code>	passed to LKT
<code>currentfixedpars</code>	used for current features as an option to start
<code>maxitv</code>	passed to LKT
<code>interc</code>	passed to LKT
<code>forward</code>	TRUE or FALSE
<code>backward</code>	TRUE or FALSE
<code>metric</code>	One of "BIC", "AUC", "AIC", and "RMSE"
<code>removefeat</code>	Character Vector Excludes specified features from the test list.
<code>removecomp</code>	Character Vector Excludes specified components from the test list.

Value

list of values "tracetable" and "currentfit"

computefeatures	<i>computefeatures</i>
-----------------	------------------------

Description

Compute feature describing prior practice effect.

Usage

```
computefeatures(data, feat, par1, par2, index, index2, par3, par4, par5, fcomp)
```

Arguments

data	copy of main data frame.
feat	is the feature to be computed.
par1	nonlinear parameters used for nonlinear features.
par2	nonlinear parameters used for nonlinear features.
index	a student by component levels index
index2	a component levels index
par3	nonlinear parameters used for nonlinear features.
par4	nonlinear parameters used for nonlinear features.
par5	nonlinear parameters used for nonlinear features.
fcomp	the component name.

Value

a vector suitable for regression input.

computeSpacingPredictors	<i>computeSpacingPredictors</i>
--------------------------	---------------------------------

Description

Compute repetition spacing time based features from input data CF.Time. and/or CF.reltime. which will be automatically computed from Duration.sec. if not present themselves.

Usage

```
computeSpacingPredictors(data, KCs)
```

Arguments

data is a dataset with Anon.Student.Id and CF..ansbin.
 KCs are the components for which spaced features will be specified in LKT

Value

data which is the same frame with the added spacing relevant columns.

countOutcomeold	<i>countOutcome</i>
-----------------	---------------------

Description

Compute the prior sum of the response appearing in the outcome column for the index

Usage

```
countOutcomeold(data, index, response)
```

Arguments

data the dataset to compute an outcome vector for
 index the subsets to count over
 response the actually response value being counted

Value

the vector of the lagged cumulative sum.

largerawsample	<i>Trial sequences for practice participants.</i>
----------------	---

Description

A dataset containing a raw sample from the Memphis DataShop.

Usage

```
largerawsample
```

Format

A data frame please see the DataShop for more info.
 It has many columns.

Source

<https://psl1datashop.web.cmu.edu/Export?datasetId=5513>

LASSOLKTDData

LASSOLKTDData

Description

Forward and backwards stepwise search for a set of features and components with tracking of nonlinear parameters.

Usage

```
LASSOLKTDData(
  data,
  gridpars,
  allcomponents,
  allfeatures,
  preset = NA,
  presetint = T,
  specialcomponents = c(),
  specialfeatures = c(),
  specialpars = c(),
  removefeat = c(),
  removecomp = c()
)
```

Arguments

data	is a dataset with Anon.Student.Id and CF.ansbin.
gridpars	a vector of parameters to create each feature at
allcomponents	is search space for LKT components
allfeatures	is search space for LKT features
preset	One of "static", "AFM", "PFA", "advanced", "AFMLLTM", "PFALLTM", "advancedLLTM"
presetint	should the intercepts be included for preset components
specialcomponents	add special components (not crossed with features, only paired with special features 1 for 1)
specialfeatures	features for each special component (not crossed during search)
specialpars	parameters for the special features (if needed)
removefeat	Character Vector Excludes specified features from the test list.
removecomp	Character Vector Excludes specified components from the test list.

Value

data which is the same frame with the added spacing relevant columns.
list of values "tracetable" and "currentfit"

LASSOLKTModel

*LASSOLKTModel***Description**

runs LASSO search on the data

Usage

```
LASSOLKTModel(
  data,
  gridpars,
  allcomponents,
  preset = NA,
  presetint = T,
  allfeatures,
  specialcomponents = c(),
  specialfeatures = c(),
  specialpars = c(),
  target_n,
  removefeat = c(),
  removecomp = c(),
  test_fold = 1
)
```

Arguments

<code>data</code>	is a dataset with Anon.Student.Id and CF.ansbin.
<code>gridpars</code>	a vector of parameters to create each feature at
<code>allcomponents</code>	is search space for LKT components
<code>preset</code>	One of "static", "AFM", "PFA", "advanced", "AFMLLTM", "PFALLTM", "advancedLLTM"
<code>presetint</code>	should the intercepts be included for preset components
<code>allfeatures</code>	is search space for LKT features
<code>specialcomponents</code>	add special components (not crossed with features, only paired with special features 1 for 1)
<code>specialfeatures</code>	features for each special component (not crossed during search)
<code>specialpars</code>	parameters for the special features (if needed)
<code>target_n</code>	chosen number of features in model
<code>removefeat</code>	Character Vector Excludes specified features from the test list.
<code>removecomp</code>	Character Vector Excludes specified components from the test list.
<code>test_fold</code>	the fold that the chosen LASSO model will be tested on

Value

list of matrices and values "train_x", "train_y", "test_x", "test_y", "fit", "target_auc", "target_rmse", "n_features", "auc_lambda", "preds"

LKT

LKT

Description

Compute a logistic regression model of learning for input data.

Usage

```
LKT(
  data,
  usefolds = NA,
  components,
  features,
  fixedpars = NA,
  seedpars = NA,
  interacts = NA,
  curvefeats = NA,
  dualfit = FALSE,
  interc = FALSE,
  verbose = TRUE,
  epsilon = 1e-04,
  cost = 512,
  lowb = 1e-05,
  highb = 0.99999,
  type = 0,
  maketimes = FALSE,
  bias = 0,
  maxitv = 100,
  factrv = 1e+12,
  nosolve = FALSE,
  autoKC = rep(0, length(components)),
  autoKCcont = rep("NA", length(components)),
  connectors = rep("+", max(1, length(components) - 1))
)
```

Arguments

data	A dataset with Anon.Student.Id and CF..ansbin.
usefolds	Numeric Vector Specifies the folds for model fitting in LKT; the features are still calculated across all folds to compute test fold fit externally
components	A vector of factors that can be used to compute each features for each subject.

features	a vector methods to use to compute a feature for the component.
fixedpars	a vector of parameters for all features+components.
seedpars	a vector of parameters for all features+components to seed non-linear parameter search.
interacts	A list of components that interacts with component by feature in the main specification.
curvefeats	vector of columns to use with "diff" functions
dualfit	TRUE or FALSE, fit a simple latency using logit. Requires Duration..sec. column in data.
interc	TRUE or FALSE, include a global intercept.
verbose	provides more output in some cases.
epsilon	passed to LiblinearR
cost	passed to LiblinearR
lowb	lower bound for non-linear optimizations
highb	upper bound for non-linear optimizations
type	passed to LiblinearR
maketimes	Boolean indicating whether to create time based features (or may be precomputed)
bias	passed to LiblinearR
maxitv	passed to nonlinear optimization a maxit control
factrv	controls the optim() function
nosolve	causes the function to return a sparse data matrix of the features, rather than a solution
autoKC	a vector to indicate whether to use autoKC for the component (0) or the k for the numebr of clusters
autoKCcont	a vector of text strings set to "rand" for component to make autoKC assignment to cluster is randomized (for comaprison)
connectors	a vector if linear equation R operators including +, * and :

Value

list of values "model", "coefs", "r2", "prediction", "nullmodel", "latencymodel", "optimizedpars", "subjectrmse", "newdata", and "automat"

LKT_HDI

LKT_HDI

Description

Bootstrap credibility intervals to aid in interpreting coefficients.

Usage

```
LKT_HDI(
  dat,
  n_boot,
  n_students,
  comps,
  feats,
  conns = rep("+", max(1, length(comps) - 1)),
  ints = NA,
  fixeds,
  get_hdi = TRUE,
  cred_mass = 0.95
)
```

Arguments

dat	Dataframe
n_boot	Number of subsamples to fit
n_students	Number of students per subsample
comps	Components in model
feats	Features in model
conns	R notation for linear equation connectors in model
ints	Interacts in model
fixeds	Fixed parameters in model
get_hdi	Boolean to decide if generating HDI per coefficient
cred_mass	Credibility mass parameter to decide width of HDI

Value

List of values "par_reps", "mod_full", "coef_hdi"

predict_lkt *Predict for LKT Models*

Description

Generates predictions and evaluates logistic regression models tailored for learning data, specifically designed for Logistic Knowledge Tracing (LKT) models. This function provides flexibility in returning either just the predicted probabilities or both the predictions and key evaluation statistics.

Usage

```
predict_lkt(
  modelob,
  data,
  fold = NULL,
  return_stats = FALSE,
  min_pred_limit = 1e-05,
  max_pred_limit = 0.99999
)
```

Arguments

modelob	An LKT model object containing necessary model coefficients and predictors for generating predictions.
data	A dataset including predictor variables, the outcome variable <code>CF..ansbin.</code> , and fold information.
fold	Optional. Numeric vector specifying which folds to include for prediction. If NULL or empty, uses all data.
return_stats	Logical. If TRUE, returns both predictions and evaluation statistics (Log-Likelihood, AUC, RMSE, R ²). If FALSE, returns only the predictions.
min_pred_limit	Minimum prediction limit. Default is 0.00001.
max_pred_limit	Maximum prediction limit. Default is 0.99999.

Value

If `return_stats` is FALSE, returns a list containing:

- `predictions`: The predicted probabilities for each observation in the specified fold(s).

If `return_stats` is TRUE, returns a list containing:

- `predictions`: The predicted probabilities for each observation in the specified fold(s).
- `LL`: Log-Likelihood of the model given the actual outcomes.
- `AUC`: Area Under the ROC Curve.
- `RMSE`: Root Mean Squared Error.
- `R2`: R-squared value, indicating the proportion of variance explained by the model.

samplelkt	<i>Trial sequences for practice participants.</i>
-----------	---

Description

A dataset containing a small sample of participants in a memory experiment.

Usage

```
samplelkt
```

Format

A data frame with 2074 rows and many variables:

Anon.Student.Id unique identifier for each student

Duration..sec. unique identifier for each student

KC..Default. unique identifier for each student

Outcome unique identifier for each student ...

Source

<https://pslcdatashop.web.cmu.edu/DatasetInfo?datasetId=5508>

smallSet	<i>smallSet</i>
----------	-----------------

Description

smallSet

Usage

```
smallSet(data, nSub)
```

Arguments

data Dataframe of student data

nSub Number of students

ViewExcel

ViewExcel

Description

ViewExcel

Usage

```
ViewExcel(df = .Last.value, file = tempfile(fileext = ".csv"))
```

Arguments

df	Dataframe
file	name of the Excel file

Index

* datasets

- largerawsample, 5
- samplelkt, 12

buildLKTModel, 2

computefeatures, 4

computeSpacingPredictors, 4

countOutcomeold, 5

largerawsample, 5

LASSOLKTData, 6

LASSOLKTModel, 7

LKT, 8

LKT_HDI, 10

predict_lkt, 11

samplelkt, 12

smallSet, 12

ViewExcel, 13